# FULL HD OVER COAX USE YOUR EXISTING COAX CABLE

HD-SDI FULL HD (1080p) IR BULLET CAMERA 3.6mm 3 Mega-Pixel Lens True Day & Night (ICR) DC 12V / 3DDNR Dual Output (HD-SDI/Analog) 24 IR LED

1080p

## **1080P OUTDOOR** INFRARED BULLET CAMERA WITH ICR

1280

DI

360 CIF 720p

720



### **DUAL OUTPUT** HD-SDI/Analog



#### **DAY & NIGHT FUNCTION**

This camera has a function that automatically selects the mode that is appropriate for daytime or night-time conditions. The COLOR mode operates in daytime conditions to provide optimum colors, and BW mode operates in nighttime conditions to enhance the difinition of the image.

#### **PRIVACY FUNCTION**

The PRIVACY function enables you to select and record only choose area among twenty-eight areas.

#### **ADDITIONAL FUNCTION**

White Balance, Motion Detection, Mirror, Sharpness, Freeze, and Digital Zoom are also available.

#### **CONTROLLED OSD MENU**

The camera can be controlled by selecting text displayed on the monitor screen.

| Solution              | 1/2.8" Mega Pixel Sensor                       |
|-----------------------|------------------------------------------------|
| Signal System         | PAL/NTSC                                       |
| Sync. System          | Internal Sync.                                 |
| Effective Pixels      | 2.0 Mega Pixels                                |
| Sensing Area          | S.42mm × 3.41 mm                               |
| Horizontal Resolution | PAL:1920×1080P 2SF/S<br>NTSC: 1920×1080P 30F/S |
| Video Output          | 1.0Vp-p75Ω                                     |
| S/N Ratio             | More than 50dB (AGC OFF)                       |
| White Balance         | Auto Tracking White Balance                    |
| Shutter Speed         | 1/25-1/50000                                   |
| Infrared Lamps        | Night/Day ON/OFF                               |
| Minimum Illumination  | 0 Lux(Infrared Lamps Turn on)                  |
| Infrared Wavelength   | 850nm                                          |
| IR Leds               | 24 Pcs                                         |
| Built-In Lens         | 3.6mm 3 Mega Pixel Lens                        |
| Working Temperature   | -10°C-50°C                                     |
| Storage Temperature   | -20°C-50°C                                     |
| Power Requirement     | DC12V                                          |